



# TECHNOSOL®

---

Due to its considerable versatility, TECHNOSOL® is an ideal detergent for all spheres of industry and car repair shops.



## USAGE

---

TECHNOSOL® removes residues of glues and sealants, solid lubricants, oils and greases containing dirt without any problems. It is especially suitable for cleaning of disc and drum brakes. It cleans electric components etc. Due to its good penetration and cleaning effects, TECHNOSOL® has a very good use in preparing surfaces for gluing, cementing and painting or for other repairing and mounting activities of similar character.

## BENEFITS

---

Very easy and quick use  
Excellent for cleaning of heavily accessible places  
It dries up quickly after application

## USER MANUAL

---

1. Agitate the container well before use.
2. Apply from the distance of about 20 – 30 cm.
3. In the case of major contamination, let the product operate for a longer time or remove rough dirt mechanically if possible.
4. The procedure can be repeated several times.

## TECHNICAL DATA

Boiling temperature:	66,7 °C
Flash point:	< -30 °C
Density (at 20 oC):	748 kg/m3
Vapor pressure (at 20 oC):	3775 mm Hg
Evaporation category (according to PN 18/10)	very quick evaporation
Evaporation rate (according to PN 18/10)	< 2 min

## CONTENT

## STOCK NUMBER

600 ml spray	200 500
--------------	---------

## RELATED PRODUCTS

APLIKAČNÍ  
PISTOLE  
CANGUN



All products of NOVATO® spol. s.r.o., which are a chemical mixture or a dangerous chemical mixture, are properly classified, marked and equipped with safety data sheets in accordance with the Chemical Act and relevant regulations within the EU. All hazardous mixtures have a safety data sheet, which is freely available on our website [www.novato.cz](http://www.novato.cz), eventually at our sales representatives and in the sales department of the company. All users of NOVATO® products are legally required to familiarize themselves with the technical and safety data sheets of the product concerned to ensure proper use, storage and handling of the product. Our oral and written technical recommendations, which we transmit with the utmost knowledge, cannot cover all details and conditions of the application and do not exempt users from their own examinations and tests in relation to third party rights. Therefore, the user is obliged to perform tests and tests for individual applications in such a way as to eliminate all risks associated with the application of the chemical mixture, especially the hazardous chemical mixture, as these applications and their conditions are beyond our control possibilities. NOVATO® spol. s.r.o. guarantees the declared quality of its products and the properties described in the technical and safety data sheets.

NOVATO® spol. s.r.o., Uralská 6, 160 00 Prague 6, tel.: +420 233 339 688, fax: +420 224 315 198, e-mail: [obchod@novato.cz](mailto:obchod@novato.cz), [www.novato.cz](http://www.novato.cz)