WATER-DILUTABLE PRODUCTS - SPECIAL





ULTRALON®

ULTRALON® is a concentrated degreaser and cleaning agent for technical use. It is non-toxic, non-flammable and biodegradable. It is used on all waterproof surfaces. It combines the advantages of organic solvents and water-soluble agents.



USAGE

ULTRALON® is used for the technical cleaning of all waterproof surfaces. It contains special organic solvents miscible with water and works very well even where other preparations fail.

BENEFITS

easy application safe to most surfaces highly effective

DOSAGE AND DILUTION

	ULTRALON	water
engines, auto parts, machine tools	1	3
heavily soiled floors, machines	1	5
food machinery and operations	1	10
high pressure and regular cleaning	1	50-100

USER MANUAL

ULTRALON® is applied by spraying, painting or dipping, after a few minutes of action it is rinsed off with water. Using a brush, brush or pressure at the same time as increasing the temperature of the working solution up to 60 °C significantly increases efficiency. Do not use on glass. For aluminum alloys, test the reaction of the ULTRALON® solution with the cleaned surface.



TECHNICAL DATA

рН	12-13
Evaporation category (dle PN 18/10)	slow evaporation
Evaporation rate(dle PN 18/10)	< 60 min

CONTENT STOCK NUMBER

25 I canister	217 025
40 I canister	217 040

All products of NOVATO* spol. s.r.o., which are a chemical mixture or a dangerous chemical mixture, are properly classified, marked and equipped with safety data sheets in accordance with the Chemical Act and relevant regulations within the EU. All hazardous mixtures have a safety data sheet, which is freely available on our website www.novato.cz, eventually at our sales representatives and in the sales department of the company. All users of NOVATO* products are legally required to familiarize themselves with the technical and safety data sheets of the product concerned to ensure proper use, storage and handling of the product. Our oral and written technical recommendations, which we transmit with the utmost knowledge, cannot cover all details and conditions of the application and do not exempt users from their own examinations and tests in relation to third party rights. Therefore, the user is obliged to perform tests and tests for individual applications in such a way as to eliminate all risks associated with the application of the chemical mixture, especially the hazardous chemical mixture, as these applications and their conditions are beyond our control possibilities. NOVATO* spol. s.r.o. guarantees the declared quality of its products and the properties described in the technical and safety data sheets.

NOVATO* spol. s.r.o., Uralská 6, 160 00 Prague 6, tel .: +420 233 339 688, fax: +420 224 315 198, e-mail: obchod@novato.cz, www.novato.cz