



# MEGA OLEJ® PLUS

MEGA OLEJ® PLUS is a highly effective penetrating oil with excellent lubricating properties for versatile use.



## USAGE

MEGA OLEJ® PLUS has excellent lubricating properties, high penetration ability and very good adhesion. It has a long-term effect, reduces wear, noise and at the same time prolongs the life of the equipment. Lubricates all types of bearings, valves, axles, threads, gears, cables, fine mechanisms, etc. It removes creaking of movably connected parts, loosens rusted bolts, nuts, hardened bearings and at the same time acts as a good corrosion protection. It has a low tendency to oxidize and is therefore particularly suitable for long-term lubrication.

## BENEFITS

stability at high temperatures  
extreme load capacity  
very sticky  
reduces friction

## USER MANUAL

Clean the application site of rust, dust and solid dirt. Remove old grease residues and degrease with TECHNOSOL®. Then apply the oil as usual.

## TECHNICAL DATA

Colour	clear
Composition	mineral oil with additives
Flash point	94 °C
Specific gravity (20 °C)	0,85 g/ml

# MEGA OLEJ<sup>®</sup> PLUS

## CONTENT

400 ml spray

## STOCK NUMBER

203 900

## RELATED PRODUCTS

TECHNOSOL<sup>®</sup>



NO 1<sup>®</sup>



NR<sup>®</sup> - INVISIBLE  
GLOVES



OTAVON<sup>®</sup>  
3000



All products of NOVATO<sup>®</sup> spol. s.r.o., which are a chemical mixture or a dangerous chemical mixture, are properly classified, marked and equipped with safety data sheets in accordance with the Chemical Act and relevant regulations within the EU. All hazardous mixtures have a safety data sheet, which is freely available on our website [www.novato.cz](http://www.novato.cz), eventually at our sales representatives and in the sales department of the company. All users of NOVATO<sup>®</sup> products are legally required to familiarize themselves with the technical and safety data sheets of the product concerned to ensure proper use, storage and handling of the product. Our oral and written technical recommendations, which we transmit with the utmost knowledge, cannot cover all details and conditions of the application and do not exempt users from their own examinations and tests in relation to third party rights. Therefore, the user is obliged to perform tests and tests for individual applications in such a way as to eliminate all risks associated with the application of the chemical mixture, especially the hazardous chemical mixture, as these applications and their conditions are beyond our control possibilities. NOVATO<sup>®</sup> spol. s.r.o. guarantees the declared quality of its products and the properties described in the technical and safety data sheets.

NOVATO<sup>®</sup> spol. s.r.o., Uralská 6, 160 00 Prague 6, tel. : +420 233 339 688, fax: +420 224 315 198, e-mail: [obchod@novato.cz](mailto:obchod@novato.cz), [www.novato.cz](http://www.novato.cz)