



## MKL®

MKL® is a specially developed dry-based lubricating sliding varnish. It is an excellent tool for unattended permanent lubrication in extreme conditions and at the same time it is used wherever it is not suitable to use common oils, Vaseline or lubricating greases.

## USAGE

MKL® is recommended as a high-quality solid assembly lubricant that dries within 5 minutes and lubricates immediately. A thin layer is enough to ensure permanent lubrication. MKL® is a dry permanent antistatic lubrication with a quick-drying sliding anti-corrosion protective film. It is ideal as a running-in or one-time lubrication. It is also used for lubrication of guide rails, slides and threaded guides on machine tools, roller tracks, shafts, bearings, gears, slides, etc.

## BENEFITS

- slows down corrosion and reduces friction
- is extremely resistant to pressure
- withstands thermal stress up to 350 ° C
- does not age or dry out
- has antistatic effects, is resistant to dust, dirt and moisture

## USER MANUAL

1. Shake the can very well before use (at least 2 minutes).
2. Thoroughly clean the substrate, remove grease and dirt, preferably with TECHNOSOL®.
3. Apply from a distance of approx. 15 - 20 cm.
4. Apply in 1 - 3 coats according to the porosity of the surface.

## TECHNICAL DATA

Boiling point 123 ° C  
Flash point <-30 ° C  
Density (20 ° C) 883 kg / m<sup>3</sup>

**CONTENT**

400 ml sprej

**STOCK NUMBER**

202 000

**RELATED PRODUCTS**

TECHNOSOL®



NO 1®



All products of NOVATO® spol. s.r.o., which are a chemical mixture or a dangerous chemical mixture, are properly classified, marked and equipped with safety data sheets in accordance with the Chemical Act and relevant regulations within the EU. All hazardous mixtures have a safety data sheet, which is freely available on our website [www.novato.cz](http://www.novato.cz), eventually at our sales representatives and in the sales department of the company. All users of NOVATO® products are legally required to familiarize themselves with the technical and safety data sheets of the product concerned to ensure proper use, storage and handling of the product. Our oral and written technical recommendations, which we transmit with the utmost knowledge, cannot cover all details and conditions of the application and do not exempt users from their own examinations and tests in relation to third party rights. Therefore, the user is obliged to perform tests and tests for individual applications in such a way as to eliminate all risks associated with the application of the chemical mixture, especially the hazardous chemical mixture, as these applications and their conditions are beyond our control possibilities. NOVATO® spol. s.r.o. guarantees the declared quality of its products and the properties described in the technical and safety data sheets.

NOVATO® spol. s.r.o., Uralská 6, 160 00 Prague 6, tel. : +420 233 339 688, fax: +420 224 315 198, e-mail: [obchod@novato.cz](mailto:obchod@novato.cz), [www.novato.cz](http://www.novato.cz)