



## NOVATES®

NOVATES® is a transparent lubricant very suitable for highly efficient lubrication at high pressures and under extremely adverse conditions. NOVATES® protects very well against corrosion and can be used in a wide range of operating temperatures from -35 °C to +285 °C.



## USAGE

NOVATES® thanks to its sparse consistency penetrates into hard-to-reach places, where it thickens. Therefore, it is very suitable for lubrication of chains, gears, conveyor belt mechanisms, toothed and helical gears, plain and ball bearings, articulated joints, lever gears, clutch mechanisms, lead screws, ropes, cableways, etc.

## BENEFITS

- excellent penetrating ability
- excellent adhesion
- resists chemical sample
- extends the life of chains

## USER MANUAL

1. Shake before use.
2. Apply from a distance of 15 - 20 cm.
3. Remove grease, dirt and grime from the application site before spraying, preferably with TECHNOSOL®

## TECHNICAL DATA

Boiling point	134,7 °C
Flash point	< -30 °C
Density (20 °C)	712 kg/m <sup>3</sup>
Vapor pressure (20 °C)	3195 mm Hg

## CONTENT

400 ml spray

## STOCK NUMBER

200 800

## RELATED PRODUCTS

TECHNOSOL®



NO 1®



All products of NOVATO® spol. s.r.o., which are a chemical mixture or a dangerous chemical mixture, are properly classified, marked and equipped with safety data sheets in accordance with the Chemical Act and relevant regulations within the EU. All hazardous mixtures have a safety data sheet, which is freely available on our website [www.novato.cz](http://www.novato.cz), eventually at our sales representatives and in the sales department of the company. All users of NOVATO® products are legally required to familiarize themselves with the technical and safety data sheets of the product concerned to ensure proper use, storage and handling of the product. Our oral and written technical recommendations, which we transmit with the utmost knowledge, cannot cover all details and conditions of the application and do not exempt users from their own examinations and tests in relation to third party rights. Therefore, the user is obliged to perform tests and tests for individual applications in such a way as to eliminate all risks associated with the application of the chemical mixture, especially the hazardous chemical mixture, as these applications and their conditions are beyond our control possibilities. NOVATO® spol. s.r.o. guarantees the declared quality of its products and the properties described in the technical and safety data sheets.

NOVATO® spol. s.r.o., Uralská 6, 160 00 Prague 6, tel. : +420 233 339 688, fax: +420 224 315 198, e-mail: [obchod@novato.cz](mailto:obchod@novato.cz), [www.novato.cz](http://www.novato.cz)