



SIL 100®

SIL 100® is a 100 % pure, silicon lubricant and parting agent which creates an antistatic, dry, slippery film. It is an indispensable aid in all maintenance shops, repair shops and garages, and it can be used in a wide scope of working temperatures from -80 °C up to 295 °C.

USAGE

SIL 100® is used for clean, non-sticky lubrication of locks, hinges, slide surfaces and fine mechanics in dusty environments, especially in the food-processing, textile and timber industry. SIL 100® leaves a clean, non-sticky, long-operating film which impregnates and protects against wet. It restores water-repelling effect of canvases, textiles, leather, plastics and metals. It is an excellent parting agent for injection moulds; it protects against adhesion of glues, paints, waxes, epoxide resins etc.

BENEFITS

- 100 % silicon
- Antistatic effect
- Dry lubrication
- An excellent parting agent

USER MANUAL

1. Agitate the container well before use.
2. Apply to a cleaned surface from the distance of about 20 cm.

TECHNICAL DATA

Boiling temperature	59 °C
Flash point	< -30 °C
Density (at 20 °C)	593 kg/m ³
Vapor pressure (at 20 °C)	3150 mm Hg

CONTENT

400 ml spray

STOCK NUMBER

201 000

RELATED PRODUCTS

TECHNOSOL®



NO 1®



All products of NOVATO® spol. s.r.o., which are a chemical mixture or a dangerous chemical mixture, are properly classified, marked and equipped with safety data sheets in accordance with the Chemical Act and relevant regulations within the EU. All hazardous mixtures have a safety data sheet, which is freely available on our website www.novato.cz, eventually at our sales representatives and in the sales department of the company. All users of NOVATO® products are legally required to familiarize themselves with the technical and safety data sheets of the product concerned to ensure proper use, storage and handling of the product. Our oral and written technical recommendations, which we transmit with the utmost knowledge, cannot cover all details and conditions of the application and do not exempt users from their own examinations and tests in relation to third party rights. Therefore, the user is obliged to perform tests and tests for individual applications in such a way as to eliminate all risks associated with the application of the chemical mixture, especially the hazardous chemical mixture, as these applications and their conditions are beyond our control possibilities. NOVATO® spol. s.r.o. guarantees the declared quality of its products and the properties described in the technical and safety data sheets.

NOVATO® spol. s.r.o., Uralská 6, 160 00 Prague 6, tel. : +420 233 339 688, fax: +420 224 315 198, e-mail: obchod@novato.cz, www.novato.cz