



MOS[®] PASTA

MOS[®] PASTA is a special lubricant designed for optimal protection of screw and impacted connections against corrosion, seizure and oxidation. MOS[®] excels in excellent adhesion and is resistant to temperatures from -40 ° C to + 1350 ° C.



USAGE

MOS[®] PASTA is used to protect metals in the most difficult conditions of industrial practice, where corrosion, wear and rust can cause damage. It is especially suitable for assembly and disassembly, where it reduces the pressure generated between the metals and thus protects the threads. MOS[®] is also an excellent lubricant for static, highly stressed parts and slow-rotating equipment at high temperatures. Resistant to rinsing with fresh and salt water, strong alkaline agents, most chemical vapors, water vapor, etc. MOS[®] PASTA is not sensitive to most gases, such as propane, butane, natural gas, helium, freon, nitrogen, etc.

BENEFITS

- prevents corrosion, oxidation and etching
- reduces material wear
- withstands high pressures
- prevents seals of joints and seals
- has excellent thermal conductivity
- greatly reduces the cost of spare parts

USER MANUAL

1. Remove corrosion and old lubricants from the treated surface (it is suitable to use the TECHNOSOL[®] product).
2. Lightly coat the area to be protected.

NOTICE

MOS[®] PASTA must not be used on oxygen cylinders and acetylene equipment.

MOS® PASTA

TECHNICAL DATA

Boiling point	123 °C
Point of ignition	< -18 °C
Density (20 °C)	795 kg/m ³
Tension par (20 °C)	3135 mm Hg

CONTENT

STOCK NUMBER

60 g pasta	200 390
500 g pasta	200 405

RELATED PRODUCTS

TECHNOSOL®



NO 1®



All products of NOVATO® spol. s.r.o., which are a chemical mixture or a dangerous chemical mixture, are properly classified, marked and equipped with safety data sheets in accordance with the Chemical Act and relevant regulations within the EU. All hazardous mixtures have a safety data sheet, which is freely available on our website www.novato.cz, eventually at our sales representatives and in the sales department of the company. All users of NOVATO® products are legally required to familiarize themselves with the technical and safety data sheets of the product concerned to ensure proper use, storage and handling of the product. Our oral and written technical recommendations, which we transmit with the utmost knowledge, cannot cover all details and conditions of the application and do not exempt users from their own examinations and tests in relation to third party rights. Therefore, the user is obliged to perform tests and tests for individual applications in such a way as to eliminate all risks associated with the application of the chemical mixture, especially the hazardous chemical mixture, as these applications and their conditions are beyond our control possibilities. NOVATO® spol. s.r.o. guarantees the declared quality of its products and the properties described in the technical and safety data sheets.

NOVATO® spol. s.r.o., Uralská 6, 160 00 Prague 6, tel. : +420 233 339 688, fax: +420 224 315 198, e-mail: obchod@novato.cz, www.novato.cz