



REZOJED®

REZOJED® is a very efficient aerosol agent intended to dissolve rust. It is mainly used for repairs in professional repair shops, maintenance workshops and electric appliances repair shops.

USAGE

REZOJED® dissolves rust even in places with very difficult access. It releases screws, nuts, pins, and it prevents squeaking very efficiently. It also reduces wear and tear, thanks to its high mechanical resistance. It does not damage varnish, rubber or glass.

BENEFITS

- Very good penetration ability
- It dissolves rust
- It releases screws, pins, nuts etc.
- It prevents squeaking and crunching

USER MANUAL

1. Agitate the container duly before use.
2. Apply from the distance of about 20 cm and let the agent operate.
3. In the case of rust-in joints, let the product operate for a longer time, and then dismount the joint.
4. It is possible to repeat the procedure several times in the case of heavier corrosion or oxidation.

TECHNICAL DATA

Boiling temperature	178 °C
Flash point	< -30 °C
Density (at 20 °C)	598 kg/m ³
TVapor pressure (at 20 °C)	3135 mm Hg

CONTENT

400 ml spray

STOCK NUMBER

200 700

RELATED PRODUCTS

MOS® PASTA



All products of NOVATO® spol. s.r.o., which are a chemical mixture or a dangerous chemical mixture, are properly classified, marked and equipped with safety data sheets in accordance with the Chemical Act and relevant regulations within the EU. All hazardous mixtures have a safety data sheet, which is freely available on our website www.novato.cz, eventually at our sales representatives and in the sales department of the company. All users of NOVATO® products are legally required to familiarize themselves with the technical and safety data sheets of the product concerned to ensure proper use, storage and handling of the product. Our oral and written technical recommendations, which we transmit with the utmost knowledge, cannot cover all details and conditions of the application and do not exempt users from their own examinations and tests in relation to third party rights. Therefore, the user is obliged to perform tests and tests for individual applications in such a way as to eliminate all risks associated with the application of the chemical mixture, especially the hazardous chemical mixture, as these applications and their conditions are beyond our control possibilities. NOVATO® spol. s.r.o. guarantees the declared quality of its products and the properties described in the technical and safety data sheets.

NOVATO® spol. s.r.o., Uralská 6, 160 00 Prague 6, tel. : +420 233 339 688, fax: +420 224 315 198, e-mail: obchod@novato.cz, www.novato.cz