



VULPA® SIL MAX

Silicone tape for quick repairs. Creates airtight and watertight joints. It offers high thermal and electrical insulation resistance, easy application even on dirty surfaces. Repairs can also be performed underwater. The tape does not contain any adhesives, leaving no traces after removal. Fixes immediately. It excels in high extensibility.



USAGE


Silicone tape for quick repairs. Creates airtight and watertight joints. It offers high thermal and electrical insulation resistance, easy application even on dirty surfaces. Repairs can also be performed underwater. The tape does not contain any adhesives, leaving no traces after removal. Fixes immediately. It excels in high extensibility.

BENEFITS

- heat resistance
- creates airtight and watertight joints
- resistance to acid, solvents, fuel, oil, salt water, UV radiation
- immediate fixation
- application even under water

USER MANUAL

1. Clean the applied area of loose dirt and cut the required length of tape.
Remove part of the protective film.
Start with one complete turn that locks the tape
Stretch the tape and rewind to the desired location with a 50% overlap. For pressure-stressed applications, VULPA® SIL MAX stretch the tape to the maximum and wind 2 or more layers.
Apply the final wrap to the already wound tape and press firmly. Fixes immediately, permanent connection within 2 minutes. The application can be performed even in a humid environment, the best results are achieved on a clean, dry surface.



TECHNICAL DATA

Tape size width 50.8 mm, length 11 meters
Tape thickness 0.8 mm
Thermal resistance -50 ° C +260 ° C
Elongation 300%
Electrical resistance 15000 V / mm
Excellent UV resistance
Tensile strength 4.1 MPa

CONTENT

STOCK NUMBER

černá	400 450
balení: 1 ks role 50,8mm x 11metrů	ROLE

All products of NOVATO® spol. s.r.o., which are a chemical mixture or a dangerous chemical mixture, are properly classified, marked and equipped with safety data sheets in accordance with the Chemical Act and relevant regulations within the EU. All hazardous mixtures have a safety data sheet, which is freely available on our website www.novato.cz, eventually at our sales representatives and in the sales department of the company. All users of NOVATO® products are legally required to familiarize themselves with the technical and safety data sheets of the product concerned to ensure proper use, storage and handling of the product. Our oral and written technical recommendations, which we transmit with the utmost knowledge, cannot cover all details and conditions of the application and do not exempt users from their own examinations and tests in relation to third party rights. Therefore, the user is obliged to perform tests and tests for individual applications in such a way as to eliminate all risks associated with the application of the chemical mixture, especially the hazardous chemical mixture, as these applications and their conditions are beyond our control possibilities. NOVATO® spol. s.r.o. guarantees the declared quality of its products and the properties described in the technical and safety data sheets.

NOVATO® spol. s.r.o., Uralská 6, 160 00 Prague 6, tel. : +420 233 339 688, fax: +420 224 315 198, e-mail: obchod@novato.cz, www.novato.cz