



WEGALUBE® ULTRA

WEGALUBE® ultra is a broad-spectrum lubricating spray with excellent lubricating properties. It works in the long term, prevents corrosion, reduces wear, expels humidity, does not damage plastics or rubber, penetrates into hardly accessible places. It reduces noise and prolongs the life of the device. It creates a molecular layer of high strength and thermal stability on the friction segments thanks to the effect of an active additive. The layer created is characterized by highly smooth surface and perfect slipperiness. It resists very high load in the friction point. It resists high thermal stress up to 400°C. It is suitable for medium to higher peripheral speeds.



USAGE

WEGALUBE® ultra is suitable for lubricating all types of bearings, chains, linear guides, valves, threads, axes, gears, threaded spindles, cable hoses, pivots, front derailleurs, toothed wheels, guide screws, ratchet mechanisms, water pumps, garden machines, sport tools, shipbuilding industry, metallurgy, engineering industry, car industry etc. It repels water, loosens movable parts and prolongs lubrication intervals considerably. It has low tendency to oxidation, and that's why it is especially suitable for long-term lubrication. It prolongs lubrication intervals. It has long-term effects.

BENEFITS

- Stability at high temperatures
- High penetration ability
- Reduces wear and tear
- Extreme load-bearing capacity
- Reduces friction
- Prolongs lubrication intervals

USER MANUAL

Remove dirt from the place of application and degrease it using TECHNOSOL®. Apply to the required place in a thin layer.

WEGALUBE® ULTRA

TECHNICAL DATA

Colour	Light brown
Composition	Petroleum product with an additive
Ignition point	More than 230°C
Self-ignition temperature	More than 390°C
Oxidizing properties	Non-oxidizing

CONTENT

Spray 400 ml	200 270
--------------	---------

STOCK NUMBER

RELATED PRODUCTS

TECHNOSOL®



All products of NOVATO® spol. s.r.o., which are a chemical mixture or a dangerous chemical mixture, are properly classified, marked and equipped with safety data sheets in accordance with the Chemical Act and relevant regulations within the EU. All hazardous mixtures have a safety data sheet, which is freely available on our website www.novato.cz, eventually at our sales representatives and in the sales department of the company. All users of NOVATO® products are legally required to familiarize themselves with the technical and safety data sheets of the product concerned to ensure proper use, storage and handling of the product. Our oral and written technical recommendations, which we transmit with the utmost knowledge, cannot cover all details and conditions of the application and do not exempt users from their own examinations and tests in relation to third party rights. Therefore, the user is obliged to perform tests and tests for individual applications in such a way as to eliminate all risks associated with the application of the chemical mixture, especially the hazardous chemical mixture, as these applications and their conditions are beyond our control possibilities. NOVATO® spol. s.r.o. guarantees the declared quality of its products and the properties described in the technical and safety data sheets.

NOVATO® spol. s.r.o., Uralská 6, 160 00 Prague 6, tel. : +420 233 339 688, fax: +420 224 315 198, e-mail: obchod@novato.cz, www.novato.cz