



# AIRSOL® - UNDERCOOLING SPRAY

AIRSOL® - undercooling spray is designed for service, repairs and troubleshooting in all fields.



## USAGE

AIRSOL® - subcooling spray can subcool parts down to -60°C. This property can be used to diagnose malfunctions in electrical installations, e.g. temperature sensors, bimetallic switches, etc. Rapid cooling also affects the thermal expansion of materials. Due to this, AIRSOL® - subcooling spray finds application in assembly and disassembly of parts, storage of ball bearings of shafts and bushings. It is intended for the repair and maintenance of machines and equipment, at the same time it can be used to perfectly remove stuck chewing gum residues.

## BENEFITS

- Suitable for assembly and disassembly
- Checking sensors and contacts
- 360° nozzle
- Subcooler for electronics
- Freezes down to -60°C

## USER MANUAL

Spray AIRSOL® - subcooling spray from a distance of approx. 15 cm on the desired place, thereby achieving its subcooling. Depending on the spray time, you can increase or decrease the freezing effect.

## NOTICE

Avoid direct contact with liquid gas - there is a risk of burns due to freezing. Never spray against the body. Follow the principles of occupational safety.

# AIRSOL<sup>®</sup> - UNDERCOOLING SPRAY

## TECHNICAL DATA

Color	transparent
Ignition temperature	470°C
Vapor pressure at 20°C	3 - 4 bar
Density at 20°C	0,65 g/ml

## CONTENT

## STOCK NUMBER

	201 410
--	---------

All products of NOVATO<sup>®</sup> spol. s.r.o., which are a chemical mixture or a dangerous chemical mixture, are properly classified, marked and equipped with safety data sheets in accordance with the Chemical Act and relevant regulations within the EU. All hazardous mixtures have a safety data sheet, which is freely available on our website [www.novato.cz](http://www.novato.cz), eventually at our sales representatives and in the sales department of the company. All users of NOVATO<sup>®</sup> products are legally required to familiarize themselves with the technical and safety data sheets of the product concerned to ensure proper use, storage and handling of the product. Our oral and written technical recommendations, which we transmit with the utmost knowledge, cannot cover all details and conditions of the application and do not exempt users from their own examinations and tests in relation to third party rights. Therefore, the user is obliged to perform tests and tests for individual applications in such a way as to eliminate all risks associated with the application of the chemical mixture, especially the hazardous chemical mixture, as these applications and their conditions are beyond our control possibilities. NOVATO<sup>®</sup> spol. s.r.o. guarantees the declared quality of its products and the properties described in the technical and safety data sheets.

NOVATO<sup>®</sup> spol. s.r.o., Uralská 6, 160 00 Prague 6, tel. : +420 233 339 688, fax: +420 224 315 198, e-mail: [obchod@novato.cz](mailto:obchod@novato.cz), [www.novato.cz](http://www.novato.cz)