



ULTRALON NH

Ultralon NH is a non-flammable degreaser for direct application in industry. Removes mineral lubricants, preservative oils, emulsion liquids, waxes, inks. Suitable for surface preparation before gluing, painting. Can be used for ultrasonic cleaning. It is characterized by residual rapid evaporation, non-aggressive odor, low VOC content, water solubility and easy application.



USER MANUAL

It is applied directly, cold, spray, immersion, brush. It is advisable to wipe the cleaned surface with a cloth, which removes excess liquid and even evaporation. In case of heavy soiling, repeat the application. The liquid is soluble in water and rinsing the surface with water can be used. Use in ultrasound is possible up to a temperature of 40 ° C at normal frequencies. Depending on the degree of contamination and the application used, the liquid can be diluted with water to a ratio of 1: 3. Test surface compatibility.

FIELDS OF APPLICATION

Residual degreaser with high degreasing power, VOC content of only 10% and rapid evaporation within 10 minutes. It does not contaminate the work environment with an aggressive odor and protects the environment due to its fully biodegradability. Significantly improves the adhesion of the surface during gluing and painting. Applicable to metals, plastics, composites, glass, rubber, etc. Does not leave smudges on the surface, does not cause oxidation. Contributes to VOC reduction and the use of flammable, aggressive chemistry.

TECHNICAL DATA

Evaporate rate	under 10 minutes
KB index:	55
Water solubility:	yes
Biodegradability:	yes
VOC content:	10%

ULTRALON NH

CONTENT	STOCK NUMBER
900 ml spray	217 600
10 l can	217 610
25 l can	217 615
200 l barrel	217 620

All products of NOVATO® spol. s.r.o., which are a chemical mixture or a dangerous chemical mixture, are properly classified, marked and equipped with safety data sheets in accordance with the Chemical Act and relevant regulations within the EU. All hazardous mixtures have a safety data sheet, which is freely available on our website www.novato.cz, eventually at our sales representatives and in the sales department of the company. All users of NOVATO® products are legally required to familiarize themselves with the technical and safety data sheets of the product concerned to ensure proper use, storage and handling of the product. Our oral and written technical recommendations, which we transmit with the utmost knowledge, cannot cover all details and conditions of the application and do not exempt users from their own examinations and tests in relation to third party rights. Therefore, the user is obliged to perform tests and tests for individual applications in such a way as to eliminate all risks associated with the application of the chemical mixture, especially the hazardous chemical mixture, as these applications and their conditions are beyond our control possibilities. NOVATO® spol. s.r.o. guarantees the declared quality of its products and the properties described in the technical and safety data sheets.

NOVATO® spol. s.r.o., Uralská 6, 160 00 Prague 6, tel. : +420 233 339 688, fax: +420 224 315 198, e-mail: obchod@novato.cz, www.novato.cz