



ELEKTROSOL®

Due to its properties, ELEKTROSOL® is used as a multipurpose cleaner for electrical and electronic equipment



USAGE

ELEKTROSOL® ensures trouble-free operation of all treated electrical components. It dissolves grease, flushes away dust and rinses oil on printed circuit boards, switches, relays, data processing equipment, radars, instrument cabinets and office equipment. It is most used for cleaning and maintenance of electric motors. Due to its chemical composition, it is inert to most plastic parts in the electrical industry, leaving no stains and rapidly evaporating. Evaporation can be accelerated by using pressurized air.

BENEFITS

- Excellent when cleaning poorly accessible places
- Efficiency
- Speed
- Leaves no stains

USER MANUAL

Shake the container before use. Apply from a distance of approx. 20-30 cm. Compressed air accelerates the cleaned area. At normal room temperature, the product evaporates in 10-15 min.

NOTICE

ELEKTROSOL® cannot be applied under voltage.

TECHNICAL DATA

Boiling point	72 °C
Point of ignition	< -30 °C
Density (20 °C)	715 kg/m ³
Vapor pressure (20 °C)	3175 mm Hg

CONTENT

STOCK NUMBER

400 ml sprej	203 000
--------------	---------

All products of NOVATO® spol. s.r.o., which are a chemical mixture or a dangerous chemical mixture, are properly classified, marked and equipped with safety data sheets in accordance with the Chemical Act and relevant regulations within the EU. All hazardous mixtures have a safety data sheet, which is freely available on our website www.novato.cz, eventually at our sales representatives and in the sales department of the company. All users of NOVATO® products are legally required to familiarize themselves with the technical and safety data sheets of the product concerned to ensure proper use, storage and handling of the product. Our oral and written technical recommendations, which we transmit with the utmost knowledge, cannot cover all details and conditions of the application and do not exempt users from their own examinations and tests in relation to third party rights. Therefore, the user is obliged to perform tests and tests for individual applications in such a way as to eliminate all risks associated with the application of the chemical mixture, especially the hazardous chemical mixture, as these applications and their conditions are beyond our control possibilities. NOVATO® spol. s.r.o. guarantees the declared quality of its products and the properties described in the technical and safety data sheets.

NOVATO® spol. s.r.o., Uralská 6, 160 00 Prague 6, tel. : +420 233 339 688, fax: +420 224 315 198, e-mail: obchod@novato.cz, www.novato.cz