



## TL® TMEŁ 350

TL® TMEŁ 350 is an excellent silicone sealant for professional use. It excels in a wide range of operating temperatures (up to 350 ° C), chemical resistance and excellent adhesion.



### USAGE

It is used for sealing flanges, motors, gearboxes, various tanks, contact planes, air conditioning, air conditioning, freezing systems, dryers, heating units, etc. It adheres perfectly, adapts and evens out any unevenness. Replaces commonly used types of seals. Resistant to acids, alkalis, oils, fuels, ozone and UV radiation. It is often used as a support seal for O-rings, hydraulic lines and for joining silicone seals. TL® TMEŁ 350 has excellent adhesion to metals (even surface-treated), glass, ceramics, concrete, rubber and most plastics.

### BENEFITS

- operating temperature range
- high adhesion
- excellent sealing ability
- chemical resistance

### USER MANUAL

1. Remove old seals and dirt from the application site, or degrease with TECHNOSOL®.
2. Prior to application, make sure that the discharge nozzle is clear and clean it if necessary.
3. Apply the sealant with a gun at temperatures from -30 ° C to 55 ° C.
4. After work, close the discharge nozzle or allow approx. 1 cm of sealant to protrude from it, depressurize the discharge gun and hang it down with the nozzle.

# TL® TMEL 350

## TECHNICAL DATA

Processing temperature	-30 °C to 55 °C
Time to form a non-sticky skin(20 °C)	10-20 min.
Temperature resistance	-70 °C to 285 °C (in the short term 350 °C)
Flash-point	450 °C
Hardness	30 Shore
Elongation	400 %
Strength	2 MPa

## CONTENT

310 ml cartridge-red

## STOCK NUMBER

580 950

## RELATED PRODUCTS

REMOVER® TAL

TECHNOSOL®

TL® PISTOLE



All products of NOVATO® spol. s.r.o., which are a chemical mixture or a dangerous chemical mixture, are properly classified, marked and equipped with safety data sheets in accordance with the Chemical Act and relevant regulations within the EU. All hazardous mixtures have a safety data sheet, which is freely available on our website [www.novato.cz](http://www.novato.cz), eventually at our sales representatives and in the sales department of the company. All users of NOVATO® products are legally required to familiarize themselves with the technical and safety data sheets of the product concerned to ensure proper use, storage and handling of the product. Our oral and written technical recommendations, which we transmit with the utmost knowledge, cannot cover all details and conditions of the application and do not exempt users from their own examinations and tests in relation to third party rights. Therefore, the user is obliged to perform tests and tests for individual applications in such a way as to eliminate all risks associated with the application of the chemical mixture, especially the hazardous chemical mixture, as these applications and their conditions are beyond our control possibilities. NOVATO® spol. s.r.o. guarantees the declared quality of its products and the properties described in the technical and safety data sheets.

NOVATO® spol. s.r.o., Uralská 6, 160 00 Prague 6, tel. : +420 233 339 688, fax: +420 224 315 198, e-mail: [obchod@novato.cz](mailto:obchod@novato.cz), [www.novato.cz](http://www.novato.cz)