



TEF®

TEF® is transparent PTFE oil in spray, with high penetrating capacities and pressure resistance. It does not contain silicone; it is usable for temperatures from -20 °C to +195 °C, up to 230 °C for a short time.



USAGE

TEF® creates a transparent PTFE layer resistant to the effects of water, pressure, and abrasion on the surface. TEF® penetrates easily to hardly accessible places, it repels humidity, lubricates, protects against corrosion and reduces component wear considerably. It is excellent for lubrication of various types of bearings, gear and ratchet mechanisms, chains, steel cables and cable hoses, locks and fine mechanisms, plastic gears, contacts, guide plates, hinges, perimeter fittings of windows and doors, etc. It is also suitable for use in dusty environments because it is almost non-sticky. It does not damage rubber or plastics.

BENEFITS

- Range of temperatures from -20 °C to +195 °C, 230 °C for a short time
- Reduces wear
- Resistant to water and pressure
- Does not contain silicone
- Prolongs the life of machines and tools

USER MANUAL

1. Remove dirt and old lubricants from the surface to be treated (TECHNOSOL® is recommended).
2. Shake the tin thoroughly before use.
3. Apply at the distance of about 25 cm.

TECHNICAL DATA

Colour	yellow
Solidification point	-20 °C
Ignition point	over 180 °C
Range of temperatures	-20 °C až 195 °C krátkodobě až 230 °C
Viscosity at 40 °C	about 40 mm ² /s
Resistance to water	0-90 °C
Protection against corrosion	corrosion degree 0
Electric strength	at least 25 kV/2.5 mm

CONTENT

STOCK NUMBER

400 ml spray

203 310

RELATED PRODUCTS

TECHNOSOL®



NO 1®



All products of NOVATO® spol. s.r.o., which are a chemical mixture or a dangerous chemical mixture, are properly classified, marked and equipped with safety data sheets in accordance with the Chemical Act and relevant regulations within the EU. All hazardous mixtures have a safety data sheet, which is freely available on our website www.novato.cz, eventually at our sales representatives and in the sales department of the company. All users of NOVATO® products are legally required to familiarize themselves with the technical and safety data sheets of the product concerned to ensure proper use, storage and handling of the product. Our oral and written technical recommendations, which we transmit with the utmost knowledge, cannot cover all details and conditions of the application and do not exempt users from their own examinations and tests in relation to third party rights. Therefore, the user is obliged to perform tests and tests for individual applications in such a way as to eliminate all risks associated with the application of the chemical mixture, especially the hazardous chemical mixture, as these applications and their conditions are beyond our control possibilities. NOVATO® spol. s.r.o. guarantees the declared quality of its products and the properties described in the technical and safety data sheets.

NOVATO® spol. s.r.o., Uralská 6, 160 00 Prague 6, tel. : +420 233 339 688, fax: +420 224 315 198, e-mail: obchod@novato.cz, www.novato.cz