



REZOJED® ULTRA

REZOJED® ULTRA is a very effective chemical rust solvent that loosens rusted joints in seconds. This product cannot normally be compared to loose rust releasers and, thanks to its chemical composition, will often help us in hopeless fighting.



USAGE

REZOJED® ULTRA thanks to its high penetration capabilities, it gets into the finest gaps, where it breaks down the rust crystals in a few seconds and removes the tight bond of the corroded layers. It often helps even in hopeless cases, where common means fail and so far only mechanical disruption of rusted joints (drilling, grinding, burning) has been used.

BENEFITS

loosens rusted bolts, nuts, etc. in seconds
has excellent penetrating ability
does not contain fats, silicones or acids
leaves no traces

USER MANUAL

1. Shake the can before use.
2. Apply to the corroded joint.
3. Leave on for 10 - 20 seconds.
4. Then quickly tighten the joint briefly and then loosen the nut or bolt with standard assembly tools.

TECHNICAL DATA

Boiling temperature	71 °C
Flash point	< -30 °C
Density (20 °C)	735 kg/m3
Vapor pressure (20 °C)	3175 mm Hg

REZOJED® ULTRA

CONTENT

400 ml spray

STOCK NUMBER

200 750

RELATED PRODUCTS

MOS® PASTA



All products of NOVATO® spol. s.r.o., which are a chemical mixture or a dangerous chemical mixture, are properly classified, marked and equipped with safety data sheets in accordance with the Chemical Act and relevant regulations within the EU. All hazardous mixtures have a safety data sheet, which is freely available on our website www.novato.cz, eventually at our sales representatives and in the sales department of the company. All users of NOVATO® products are legally required to familiarize themselves with the technical and safety data sheets of the product concerned to ensure proper use, storage and handling of the product. Our oral and written technical recommendations, which we transmit with the utmost knowledge, cannot cover all details and conditions of the application and do not exempt users from their own examinations and tests in relation to third party rights. Therefore, the user is obliged to perform tests and tests for individual applications in such a way as to eliminate all risks associated with the application of the chemical mixture, especially the hazardous chemical mixture, as these applications and their conditions are beyond our control possibilities. NOVATO® spol. s.r.o. guarantees the declared quality of its products and the properties described in the technical and safety data sheets.

NOVATO® spol. s.r.o., Uralská 6, 160 00 Prague 6, tel. : +420 233 339 688, fax: +420 224 315 198, e-mail: obchod@novato.cz, www.novato.cz