



## ZOS®

ZOS® je speciální, vysoce účinný aerosolový výrobek, který zajišťuje katodovou, mechanickou a chemickou ochranu kovů proti korozi a je vynikající jako ochrana po svařování na galvanizované i na normální oceli.

## USAGE

ZOS® je díky svým jedinečným chemickým vlastnostem velmi vhodný při povrchové ochraně ocelových konstrukcí. Je vhodný i na ochranu míst extrémně tepelně namáhaných a díky dobré elektrické vodivosti je vhodný pro předúpravu povrchů určených pro bodové svařování. ZOS® je zároveň velmi vhodný jako základová vrstva pro veškeré druhy nátěrů.

## BENEFITS

- vynikající ochrana proti korozi
- odolnost do 400 °C
- galvanizace za studena
- výborná přilnavost

## USER MANUAL

1. Podklad zbavte koroze, dokonale očistěte, osušte a odmastěte výrobkem TECHNOSOL®.
2. Před použitím dózu důkladně protřepejte.
3. Nanášejte při pokojové teplotě ze vzdálenosti cca 25 cm.
4. Po použití obraťte nádobu dnem vzhůru a krátce stlačte ventilek tak, aby se pročistil hnacím plynem.

## TECHNICAL DATA

|                   |                       |
|-------------------|-----------------------|
| Teplota varu      | 123 °C                |
| Bod vzplanutí     | < -18 °C              |
| Hustota (20 °C)   | 795 kg/m <sup>3</sup> |
| Tenze par (20 °C) | 3135 mm Hg            |

## CONTENT

400 ml sprej

## STOCK NUMBER

200 900

## RELATED PRODUCTS

APLIKAČNÍ  
PISTOLE  
CANGUN



TECHNOSOL®



NO 1®



All products of NOVATO® spol. s.r.o., which are a chemical mixture or a dangerous chemical mixture, are properly classified, marked and equipped with safety data sheets in accordance with the Chemical Act and relevant regulations within the EU. All hazardous mixtures have a safety data sheet, which is freely available on our website [www.novato.cz](http://www.novato.cz), eventually at our sales representatives and in the sales department of the company. All users of NOVATO® products are legally required to familiarize themselves with the technical and safety data sheets of the product concerned to ensure proper use, storage and handling of the product. Our oral and written technical recommendations, which we transmit with the utmost knowledge, cannot cover all details and conditions of the application and do not exempt users from their own examinations and tests in relation to third party rights. Therefore, the user is obliged to perform tests and tests for individual applications in such a way as to eliminate all risks associated with the application of the chemical mixture, especially the hazardous chemical mixture, as these applications and their conditions are beyond our control possibilities. NOVATO® spol. s.r.o. guarantees the declared quality of its products and the properties described in the technical and safety data sheets.

NOVATO® spol. s.r.o., Uralská 6, 160 00 Prague 6, tel. : +420 233 339 688, fax: +420 224 315 198, e-mail: [obchod@novato.cz](mailto:obchod@novato.cz), [www.novato.cz](http://www.novato.cz)