



ELEKTROSOL® L

ELEKTROSOL® L se díky svým vlastnostem používá jako víceúčelový čisticí prostředek elektrických a elektronických zařízení.

USAGE

ELEKTROSOL® L zajišťuje bezporuchový chod všech ošetřených elektrických součástí. Rozpouští mastnotu, odplavuje prach a smývá olej na destičkách s plošnými spoji, vypínačích, relé, zařízeních na zpracování dat, radarech, přístrojových skříních a kancelářských zařízeních. Největší využití nachází při čištění a údržbě elektromotorů. Díky svému chemickému složení je netečný k většině plastových částí v elektroprůmyslu, přičemž nezanechává skvrny a rychle se vypařuje. Odpařování lze urychlit použitím tlakového vzduchu.

BENEFITS

- výborný při čištění špatně přístupných míst
- rychlost
- účinnost
- nezanechává skvrny

USER MANUAL

1. Před použitím dózu protřepejte.
2. Nanášejte ze vzdálenosti cca 20–30 cm.
3. Vysychání čištěného místa urychlíte tlakovým vzduchem.
4. Při běžné pokojové teplotě se výrobek odpařuje za 10–15 min.

NOTICE

ELEKTROSOL® není možné aplikovat pod napětím.

TECHNICAL DATA

Teplota varu	72 °C
Bod vzplanutí	< -30 °C
Hustota (20 °C)	715 kg/m ³
Tenze par (20 °C)	3175 mm Hg

CONTENT

STOCK NUMBER

30 l kanýstr	202 986
--------------	---------

All products of NOVATO® spol. s.r.o., which are a chemical mixture or a dangerous chemical mixture, are properly classified, marked and equipped with safety data sheets in accordance with the Chemical Act and relevant regulations within the EU. All hazardous mixtures have a safety data sheet, which is freely available on our website www.novato.cz, eventually at our sales representatives and in the sales department of the company. All users of NOVATO® products are legally required to familiarize themselves with the technical and safety data sheets of the product concerned to ensure proper use, storage and handling of the product. Our oral and written technical recommendations, which we transmit with the utmost knowledge, cannot cover all details and conditions of the application and do not exempt users from their own examinations and tests in relation to third party rights. Therefore, the user is obliged to perform tests and tests for individual applications in such a way as to eliminate all risks associated with the application of the chemical mixture, especially the hazardous chemical mixture, as these applications and their conditions are beyond our control possibilities. NOVATO® spol. s.r.o. guarantees the declared quality of its products and the properties described in the technical and safety data sheets.

NOVATO® spol. s.r.o., Uralská 6, 160 00 Prague 6, tel. : +420 233 339 688, fax: +420 224 315 198, e-mail: obchod@novato.cz, www.novato.cz