



UNISPRAY®

UNISPRAY® je výrobek, který odpuzuje vlhkost, maže, uvolňuje rez, chrání proti korozi a čistí. Proto je nepostradatelným pomocníkem při opravách a údržbě ve všech dílnách.



USAGE

UNISPRAY® je mimořádně vodoodpudivý, a proto je určen k ošetřování elektrických kabelů, zapalovacích zařízení dopravních prostředků apod. Zamezuje vzniku zkratů a plíživých proudů v el. zařízeních. Dlouhodobě chrání před vznikem oxidace a zareznutím. Vzhledem ke svým mazacím schopnostem se velmi dobře uplatní při mazání jemné mechaniky. Pronikací schopnost výrobku UNISPRAY® pro uvolňování zarezlých, zapečených nebo pevně dotažených spojů.

BENEFITS

- odstraňuje vlhkost z el. zařízení
- maže jemnou mechaniku
- uvolňuje zarezlé a zapečené spoje
- má čistící účinek

USER MANUAL

1. Před použitím dózu protřepejte.
2. Výrobek můžete aplikovat jen na el. zařízení odpojená od sítě!
3. U zarezlých spojů nechte působit a následně demontujte.
4. V případě silnějšího zareznutí nebo oxidace postup opakujte několikrát.

TECHNICAL DATA

Teplota varu	179 °C
Bod vzplanutí	< -30 °C
Bod tuhnutí	-57 °C
Hustota (20 °C)	598 kg/m ³
Tenze par (20 °C)	3135 mm Hg
Elektrická pevnost	> 30 kV/cm za min (ASTM D8777)

CONTENT

STOCK NUMBER

400 ml sprej	200 200
--------------	---------

All products of NOVATO® spol. s.r.o., which are a chemical mixture or a dangerous chemical mixture, are properly classified, marked and equipped with safety data sheets in accordance with the Chemical Act and relevant regulations within the EU. All hazardous mixtures have a safety data sheet, which is freely available on our website www.novato.cz, eventually at our sales representatives and in the sales department of the company. All users of NOVATO® products are legally required to familiarize themselves with the technical and safety data sheets of the product concerned to ensure proper use, storage and handling of the product. Our oral and written technical recommendations, which we transmit with the utmost knowledge, cannot cover all details and conditions of the application and do not exempt users from their own examinations and tests in relation to third party rights. Therefore, the user is obliged to perform tests and tests for individual applications in such a way as to eliminate all risks associated with the application of the chemical mixture, especially the hazardous chemical mixture, as these applications and their conditions are beyond our control possibilities. NOVATO® spol. s.r.o. guarantees the declared quality of its products and the properties described in the technical and safety data sheets.

NOVATO® spol. s.r.o., Uralská 6, 160 00 Prague 6, tel. : +420 233 339 688, fax: +420 224 315 198, e-mail: obchod@novato.cz, www.novato.cz