

The safety data sheet complies with Commission Regulation (EU) 878/2020 of 18 June 2020 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorization and Restriction of Chemicals (REACH) .

SOLBON

Creation date	22nd October 2003	Version	15
Revision date	16th December 2022		

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier SOLBON
Substance / mixture mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against
Mixture's intended use

Cleaning spray

The use descriptors

IS Use at industrial sites

PW Widespread use by professional workers

Mixture uses advised against

The product should not be used in ways other than those referred in Section 1.

1.3. Details of the supplier of the safety data sheet

Supplier

Name or trade name	NOVATO
Address	Uralská 770/6, Praha, 160 00 Czech Republic
Identification number (CRN)	62910370
VAT Reg No	CZ62910370
Phone	+420 233 339 688
E-mail	petr.johanides@novato.cz
Web address	www.novato.cz

Competent person responsible for the safety data sheet

Name	ABITEC
E-mail	info@abitec.cz

1.4. Emergency telephone number

European emergency number: 112

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification of the mixture in accordance with Regulation (EC) No 1272/2008

The mixture is classified as dangerous.

Aerosol 1, H229, H222

Skin Irrit. 2, H315

Eye Irrit. 2, H319

STOT SE 3, H336

Aquatic Chronic 2, H411

Most serious adverse physico-chemical effects

The mixture is extremely flammable. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 ° C. Do not puncture or throw an empty container into a fire. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of reach of children.

Most serious adverse effects on human health and the environment

Inhalation of the aerosol may cause headaches, fatigue, drowsiness. Do not breathe aerosol. Frequent or prolonged skin contact causes dryness or cracking of the skin to dermatitis. Ingestion of the liquid phase can cause abdominal pain and nausea. Follow the instructions in the operating instructions. The mixture is classified as harmful to the environment. Follow the instructions for use to avoid risks to humans and the environment. The liquid is lighter than water and can cover the water surface. The mixture must not get into the soil, groundwater or surface water or sewage system. For the full text of the H-Statements mentioned in this Section, see Section 16 of this Safety Data Sheet.

The safety data sheet complies with Commission Regulation (EU) 878/2020 of 18 June 2020 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorization and Restriction of Chemicals (REACH) .

SOLBON

Creation date	22nd October 2003	Version	15
Revision date	16th December 2022		

2.2. Label elements

Hazard pictogram



Signal word

Danger

Hazard statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P261	Avoid breathing vapours/spray.
P273	Avoid release to the environment.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

2.3. Other hazards

Neither the mixture nor its components meet the criteria for persistent, bioaccumulative and toxic or highly persistent and highly bioaccumulative substances in accordance with Annex XIII, nor have they been included in the list drawn up in accordance with Article 59, paragraph 1, due to the content of endocrine disruptors , nor has it been determined as a substance with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixture.

Mixture contains these hazardous substances and substances with the highest permissible concentration in the working environment

Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note
Index: 649-328-00-1 CAS: 64742-49-0 EC: 265-151-9	Naphtha (petroleum), hydrotreated light	50-55	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Chronic 2, H411 Specific concentration limit: Aquatic Chronic 2, H411: C ≥ 25 % STOT SE 3, H336: C ≥ 20 % Skin Irrit. 2, H315: C ≥ 10 %	3, 4, 5
Index: 601-003-00-5 CAS: 74-98-6 EC: 200-827-9	propane	26-30	Press. Gas, Flam. Gas 1, H220	2, 4

SAFETY DATA SHEET

The safety data sheet complies with Commission Regulation (EU) 878/2020 of 18 June 2020 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorization and Restriction of Chemicals (REACH) .

SOLBON

Creation date	22nd October 2003	Version	15
Revision date	16th December 2022		

Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note
Index: 601-004-00-0 CAS: 106-97-8 EC: 203-448-7	butane	26-30	Press. Gas, Flam. Gas 1, H220	1, 2, 4
Index: 601-004-00-0 CAS: 75-28-5 EC: 200-857-2	isobutane	26-30	Flam. Gas 1, H220 Press. Gas (compressed gas), H280	1, 2
Index: 606-001-00-8 CAS: 67-64-1 EC: 200-662-2	acetone	16-25	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066 Specific concentration limit: Eye Irrit. 2, H319: C ≥ 10 % STOT SE 3, H336: C ≥ 20 %	4

Notes

- 1 Note C: Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.
- 2 Note U (Table 3): When put on the market gases have to be classified as "Gases under pressure", in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case. The following codes are assigned:
 - Press. Gas (Comp.)
 - Press. Gas (Liq.)
 - Press. Gas (Ref. Liq.)
 - Press. Gas (Diss.)
- 3 Note P: The harmonised classification as a carcinogen or mutagen applies unless it can be shown that the substance contains less than 0,1 % w/w benzene (Einecs No 200-753-7), in which case a classification in accordance with Title II of this Regulation shall be performed also for those hazard classes. Where the substance is not classified as a carcinogen or mutagen, at least the precautionary statements (P102-)P260-P262-P301 + P310-P331 shall apply.
- 4 A substance for which exposure limits are set.
- 5 Fulfilled Note P

Full text of all classifications and hazard statements is given in the section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of health problems or in case of doubt, consult a physician and provide him with the information in this safety data sheet. In case of life-threatening conditions, perform resuscitation. Keep unconscious person in a stabilized position and do not give anything by mouth. Avoid cooling. Do not induce vomiting. In case of spontaneous vomiting, avoid inhalation of vomitus. If burns occur, cool the burn with cold water and cover with a clean cloth.

If inhaled

If inhaled, leave the area, rinse the mouth with water, inhale fresh air. If breathing is difficult, give first aid and seek medical advice.

If on skin

Wipe the product, wash thoroughly with lukewarm water, soap and treat with regenerating cream. If clothing is contaminated, remove clothing. Seek medical attention if irritation develops.

If in eyes

If the affected person has contact lenses, remove them. Flush eyes wide open from the inner corner of the eye towards the outside with plenty of clean lukewarm water, especially the area under the eyelids. Rinse for at least 15 minutes, seek medical attention.

The safety data sheet complies with Commission Regulation (EU) 878/2020 of 18 June 2020 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorization and Restriction of Chemicals (REACH) .

SOLBON

Creation date	22nd October 2003	Version	15
Revision date	16th December 2022		

If swallowed

In the case of an aerosol product, ingestion is very unlikely. Do not induce vomiting, rinse mouth with water. Seek medical attention immediately and present this safety data sheet. Danger of vomiting!

4.2. Most important symptoms and effects, both acute and delayed

If inhaled

Inhaling the aerosol can cause headaches, fatigue, drowsiness, malaise and even narcotic conditions, exceptional irritation of the mucous membranes and respiratory tract. Do not inhale the aerosol.

If on skin

Frequent or prolonged skin contact causes dryness or cracking of the skin to dermatitis.

If in eyes

Irritating to the eyes (watering, burning, itching, redness, conjunctivitis).

If swallowed

not available

4.3. Indication of any immediate medical attention and special treatment needed

Immediate medical attention is not required during normal use of the mixture. Required only if symptoms reach a certain level, as indicated in paragraphs 4.1 and 4.2; is symptomatic.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Multipurpose powders, CO₂, foam, water mist, sand.

Unsuitable extinguishing media

Full stream of water. Crushed water can be used to cool the containers near the fire.

5.2. Special hazards arising from the substance or mixture

Extremely flammable mixture. Incomplete combustion or thermal decomposition can produce toxic gases (CO_x, hydrocarbons, thick smoke, etc.). Do not inhale decomposition products. Vapors are heavier than air, accumulate in lower positions, can spread over long distances. When mixed with air, they can form an explosive mixture. Danger of re-ignition. There is a risk of the pressure vessel exploding at higher temperatures.

5.3. Advice for firefighters

Isolation breathing apparatus and non-flammable intervention suit. Use non-sparking tools. Cool containers exposed to fire with water spray or foam. Burning residues and post-intervention water should be disposed of as hazardous waste.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Prevent unauthorized entry, ensure free escape. Ensure adequate ventilation, do not breathe aerosol. Eliminate possible sources of ignition, do not smoke, do not handle open flame, do not expose to direct sunlight. Use non-sparking tools, avoid electrostatic charge. Avoid contact with skin and eyes - use personal protective equipment.

6.2. Environmental precautions

Provide a spill area, prevent leakage into drains, soil, surface and ground water. In case of a large liquid leak, monitor the NPK concentrations resp. TLV and inform the relevant public authorities and the flow or sewerage manager.

6.3. Methods and material for containment and cleaning up

Stop the leak. In case of large leakage of liquid fraction, drain the mixture. The aerosol evaporates, ensure adequate ventilation. In case of a minor leakage of the liquid fraction, cover with a non-flammable sorbent (sand, diatomaceous earth, soil, universal sorbent, etc.), store the used sorbent in a closable waste container, mark it and dispose of it as hazardous waste. Wash contaminated area with water.

6.4. Reference to other sections

See the Section 7, 8 and 13.

SAFETY DATA SHEET

The safety data sheet complies with Commission Regulation (EU) 878/2020 of 18 June 2020 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorization and Restriction of Chemicals (REACH) .

SOLBON

Creation date	22nd October 2003	Version	15
Revision date	16th December 2022		

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Ensure adequate ventilation of the work area. Avoid contact with open flames and other sources of ignition. Protect against direct sunlight. Use non-sparking tools. Take precautionary measures against static discharge. Avoid the formation of gases and vapors in flammable or explosive concentrations and concentrations exceeding the maximum permissible concentrations (NPK-P) for the working atmosphere. Protect eyes and skin, do not breathe aerosol or fumes, use personal protective equipment according to section 8. Observe valid legal regulations on safety and health protection. Follow the principles of hygiene when working with chemicals, do not eat, drink or smoke while working. Wash hands with warm soap and water before breaks, meals and after work.

7.2. Conditions for safe storage, including any incompatibilities

Store in original containers at temperatures up to 50 ° C in dry, well-ventilated areas. Store away from heat, protect from direct sunlight and external weather conditions. Store away from food, drink and animal feeding stuffs. Store separately as flammable. No smoking. Observe the general regulations for storage of pressure vessels. Follow the instructions on the label.

Content	Packaging type	Material of package
600 ml	aerosol can	FE
Storage class	2B - Aerosols	
Storage temperature	max. 50 °C	

7.3. Specific end use(s)

It is not.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Ensure compliance with governmental regulation 361/2007 Coll., Laying down the conditions for the protection of health at work, as amended, and to fulfill the obligations contained therein.

Czech Republic

Government Regulation 330/2023 Coll.

Substance name (component)	Type	Value	Note
Gasolines (technical mixture of hydrocarbons) (CAS: 64742-49-0)	PEL	400 mg/m ³	
	NPK-P	1000 mg/m ³	
Propane LPG (CAS: 74-98-6)	PEL	1800 mg/m ³	
	NPK-P	4000 mg/m ³	
Butane LPG (CAS: 106-97-8)	PEL	1800 mg/m ³	
	NPK-P	4000 mg/m ³	
acetone (CAS: 67-64-1)	PEL	800 mg/m ³	irritating to mucous membranes (eyes, respiratory system) and skin
	PEL	331,4 ppm	
	NPK-P	1500 mg/m ³	
	NPK-P	621,4 ppm	

European Union

Commission Directive 2000/39/EC

Substance name (component)	Type	Value	Note
acetone (CAS: 67-64-1)	OEL 8 hours	1210 mg/m ³	

The safety data sheet complies with Commission Regulation (EU) 878/2020 of 18 June 2020 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorization and Restriction of Chemicals (REACH) .

SOLBON

Creation date	22nd October 2003	Version	15
Revision date	16th December 2022		

European Union

Commission Directive 2000/39/EC

Substance name (component)	Type	Value	Note
acetone (CAS: 67-64-1)	OEL 8 hours	500 ppm	

8.2. Exposure controls

Ensure sufficient ventilation or extraction of the work area. In case of exceeding the NPK-P, use suitable respiratory protection. Avoid contact with skin and eyes, do not inhale aerosols, gases and vapors. Observe hygienic measures when working with chemicals. Do not eat, drink and smoke during work. Wash hands with lukewarm soap and water before breaks, meals and after work. Adapt personal protective equipment to the nature of the work.

Eye/face protection

Closed safety glasses.

Skin protection

Work clothes. Take off contaminated clothing and wash before reuse. In case of long-term or repeated exposure, use protective gloves (material eg nitrile, 0.4 mm; viton, 0.7 mm, penetration time > 480 min.), Or other according to the performed test. When choosing, follow the manufacturer's recommendations, the material must be impermeable and resistant to the components of the mixture. Replace damaged gloves.

Respiratory protection

It is not necessary under normal conditions. In case of increased risk of inhalation and insufficient ventilation use a mask with a filter against organic vapors and aerosols, type A. In the event of an accident or for long-term exposure, use a self-contained breathing apparatus.

Thermal hazard

Exposure to elevated temperatures may result in tearing of the aerosol container when overheating.

Environmental exposure controls

It is not necessary if handling conditions are observed. Observe normal environmental precautions, do not allow to enter drains, soil or water sources.

More information

Ensure compliance with governmental regulation 361/2007 Coll., Laying down the conditions for the protection of health at work, as amended, and to fulfill the obligations contained therein.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	liquid
Colour	colourless
Odour	characteristic
Melting point/freezing point	data not available
Boiling point or initial boiling point and boiling range	45-95 °C (liquid fraction)
Flammability	Flammable Class I.
Lower and upper explosion limit	
bottom	1 %
upper	6 %
Flash point	data not available
Auto-ignition temperature	>230 °C
Decomposition temperature	data not available
pH	data not available
Kinematic viscosity	data not available
Solubility in water	insoluble
Partition coefficient n-octanol/water (log value)	data not available
Vapour pressure	550 hPa at 20 °C (liquid fraction)
Density and/or relative density	
Density	0.69 g/cm ³ at 20 °C
Relative vapour density	data not available
Particle characteristics	data not available

The safety data sheet complies with Commission Regulation (EU) 878/2020 of 18 June 2020 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorization and Restriction of Chemicals (REACH) .

SOLBON

Creation date	22nd October 2003	Version	15
Revision date	16th December 2022		

9.2. Other information

Soluble in common organic solvents.
 VOC content 100 %
 Vapor pressure (at 20 °C): 250 kPa (incl. propellant)
 Explosive properties: Not explosive.
 Solvent vapors can form an explosive mixture when mixed with air.
 Oxidizing properties: The mixture is not classified as oxidizing.

SECTION 10: Stability and reactivity

10.1. Reactivity

The mixture is flammable. In normal conditions, the mixture does not show dangerous reactions.

10.2. Chemical stability

The mixture is stable under normal environmental conditions, storage and handling.

10.3. Possibility of hazardous reactions

No dangerous reactions are known. There is a risk of pressure explosion when exposed to high temperatures containers. Solvent vapors can form an explosive mixture when mixed with air.

10.4. Conditions to avoid

Temperatures above 50 °C, contact with open flames, possible sources of ignition and hot surfaces, sparks, static electricity. Avoid the formation of a concentration within explosive limits.

10.5. Incompatible materials

Flammable materials, strong oxidizing agents, strong acids and alkalis.

10.6. Hazardous decomposition products

Under normal conditions, the mixture does not decompose. Imperfect combustion or thermal decomposition produces toxic combustion products: COx, heavy smoke, hydrocarbons, etc.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

The mixture meets the criteria for classification according to EC Regulation No. 1272/2008. The mixture is classified as dangerous in the sense of EC Regulation No. 1272/2008, as amended.

Acute toxicity

The mixture is not classified as acutely toxic by any way of exposure.

acetone					
Route of exposure	Parameter	Value	Exposure time	Species	Sex
Oral	LD ₅₀	5800 mg/kg		Rat	
Dermal	LD ₅₀	20000 mg/kg		Rat	
Inhalation	LD ₅₀	39 mg/m ³	4 hours	Rat	

butane					
Route of exposure	Parameter	Value	Exposure time	Species	Sex
Inhalation	LC ₅₀	658 mg/l	4 hours	Rat	

Naphtha (petroleum), hydrotreated light					
Route of exposure	Parameter	Value	Exposure time	Species	Sex
Oral	LD ₅₀	>5840 mg/kg		Rat	
Dermal	LD ₅₀	>2920 mg/kg		Rabbit	
Inhalation	LC ₅₀	25.2 mg/l	4 hours	Rat	
Inhalation	LC ₅₀	193 mg/m ³	4 hours	Rat (Rattus norvegicus)	

SAFETY DATA SHEET

The safety data sheet complies with Commission Regulation (EU) 878/2020 of 18 June 2020 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorization and Restriction of Chemicals (REACH) .

SOLBON

Creation date	22nd October 2003	Version	15
Revision date	16th December 2022		

propane					
Route of exposure	Parameter	Value	Exposure time	Species	Sex
Inhalation	LC ₅₀	658 mg/l	4 hours	Rat	

Skin corrosion/irritation

The mixture is classified as skin irritant, category 2.

Serious eye damage/irritation

Mixture is classified as eye irritant, category 2..

Respiratory or skin sensitisation

Based on available data the classification criteria are not met.

Germ cell mutagenicity

Based on available data the classification criteria are not met.

Carcinogenicity

Based on available data the classification criteria are not met.

Reproductive toxicity

Based on available data the classification criteria are not met.

Toxicity for specific target organ - single exposure

The mixture is classified as toxic to specific target organs after single exposure, category 3. Inhalation of vapors or aerosol can cause headache, drowsiness or dizziness, malaise, up to narcotic states.

Toxicity for specific target organ - repeated exposure

Based on available data the classification criteria are not met.

Aspiration hazard

Based on available data the classification criteria are not met.

11.2. Information on other hazards

Inhalation of vapors can cause headaches, dizziness, malaise, fatigue and general weakness, up to narcotic states, in extreme cases loss of consciousness at high exposure. May cause severe irritation eyes (redness, burning in the eyes, tearing) and skin (redness, itching). Frequent or prolonged contact with the skin can cause drying or even skin disease. Ingestion of the liquid phase may cause irritation digestive tract, abdominal pain and nausea. Entry of liquid into the respiratory system by ingestion or aspiration of vomitus with subsequent vomiting may cause bronchopneumonia or pulmonary edema.

SECTION 12: Ecological information

12.1. Toxicity

The ecotoxic effects of the mixture were not assessed. Observe the usual environmental precautions.

Acute toxicity

acetone				
Parameter	Value	Exposure time	Species	Environment
LC ₅₀	5540 mg/l	96 hours	Fish	
EC ₅₀	8800 mg/l	48 hours	Invertebrates (Daphnia magna)	

SAFETY DATA SHEET

The safety data sheet complies with Commission Regulation (EU) 878/2020 of 18 June 2020 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorization and Restriction of Chemicals (REACH) .

SOLBON

Creation date	22nd October 2003	Version	15
Revision date	16th December 2022		

acetone				
Parameter	Value	Exposure time	Species	Environment
LC ₅₀	903 mg/l		Invertebrates (Crangon crangon)	
EC ₅₀	>10 g/l	48 hours	Invertebrates (Daphnia magna)	

Naphtha (petroleum), hydrotreated light				
Parameter	Value	Exposure time	Species	Environment
LC ₅₀	93-117 mg/l	96 hours	Fish	
EC ₅₀	4.3 mg/l	96 hours	Invertebrates (Daphnia magna)	
LC ₅₀	2200 mg/l	96 hours	Fish (Pimephales promelas)	
EC ₅₀	30-100 mg/l	72 hours	Algae	

12.2. Persistence and degradability

Data not available.

12.3. Bioaccumulative potential

Not determined, bioaccumulation is unlikely.

12.4. Mobility in soil

The mixture evaporates easily.

12.5. Results of PBT and vPvB assessment

The mixture does not contain substances from the PBT and vPvB groups according to Annex XIII of the REACH Regulation, as amended.

12.6. Endocrine disrupting properties

Substances with these properties in accordance with the criteria set out in Commission Regulation (EU) 2017/2100 or (EU) 2018/605 are not included.

12.7. Other adverse effects

Water hazard class: 2 (Self-classification): Harmful to water. The mixture is dangerous for the environment, even if small quantities can contaminate drinking water sources. Do not get into the ground, underground or surface water or sewers. Observe the usual precautions to protect the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Dispose of as hazardous waste. Dispose of at an authorized person or to a hazardous waste collection yard. Dispose of mixture and packaging residues in accordance with local waste disposal regulations. Dispose of contaminated packaging as hazardous waste.

Waste management legislation

Act No. 477/2001 Coll., On Packaging, as amended. Directive 2008/98/EC of the European Parliament and of the Council of 19 November 2008 on waste, as amended.

Waste type code

14 06 03* other solvents and solvent mixtures

16 05 06* laboratory chemicals, consisting of or containing hazardous substances, including mixtures of laboratory chemicals

Packaging waste type code

15 01 11* metallic packaging containing a hazardous solid porous matrix (for example asbestos), including empty pressure containers

15 01 10* packaging containing residues of or contaminated by hazardous substances

(*) - Hazardous waste according to Directive 2008/98/EC on hazardous waste

The safety data sheet complies with Commission Regulation (EU) 878/2020 of 18 June 2020 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorization and Restriction of Chemicals (REACH) .

SOLBON

Creation date	22nd October 2003	Version	15
Revision date	16th December 2022		

SECTION 14: Transport information

14.1. UN number or ID number

UN 1950

14.2. UN proper shipping name

AEROSOLS

14.3. Transport hazard class(es)

2 Gases

14.4. Packing group

not relevant

14.5. Environmental hazards

No.

14.6. Special precautions for user

Transport in packages that match the properties of the mixture. Observe the prescribed marking for cargo.

14.7. Maritime transport in bulk according to IMO instruments

Can not be used.

Additional information

Hazard identification No.

UN number

Classification code

Safety signs



5F

2.1+hazardous for the environment



Road transport - ADR

Special provisions 190, 327, 344, 625

Limited quantities 1 L

Excepted quantities E0

Packaging

Packing instructions P207, LP200

Special packing provisions PP87, RR6, L2

Mixed packing provisions MP9

Transport category 2

Tunnel restriction code (D)

Special provision for

packages V14

loading, unloading and handling CV9, CV12

operation S2

Railway transport - RID

Special provisions 190, 327, 344, 625

Excepted quantities E0

Packaging

Packing instructions P207, LP200

Special packing provisions PP87, RR6, L2

Mixed packing provisions MP9

Transport category 0

Special provision for

packages W14

loading, unloading and handling CW9, CW12

SAFETY DATA SHEET

The safety data sheet complies with Commission Regulation (EU) 878/2020 of 18 June 2020 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorization and Restriction of Chemicals (REACH) .

SOLBON

Creation date	22nd October 2003	Version	15
Revision date	16th December 2022		

Air transport - ICAO/IATA

Packaging instructions for limited amount	Y203
Packaging instructions passenger	203
Cargo packaging instructions	203

Marine transport - IMDG

EmS (emergency plan)	F-D, S-U
MFAG	6F0

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Parliament and of the Council of 18th December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing the European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No. 793/93 and Commission Regulation (EC) No. 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, as amended. COMMISSION REGULATION (EU) 2020/878 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorization and Restriction of Chemicals (REACH). Commission Delegated Regulation (EU) 2021/849 of 11 March 2021 amending, for the purposes of adapting to technical and scientific progress, Part 3 of Annex VI to Regulation (EC) No 1272/2008 of the European Parliament and of the Council on classification, labeling and packaging of substances and mixtures. REGULATION (EC) No 648/2004 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 31 March 2004 on detergents, as amended. Commission Regulation (EU) No 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorization and Restriction of Chemicals.

15.2. Chemical safety assessment

No chemical hazard assessment was performed for this mixture.

More information

This information only indicates the basic regulations listed in this Safety Data Sheet. Please note the possible existence of additional regulations supplementing these Regulations. We refer to all applicable national, international and local regulations and regulations.

SECTION 16: Other information

A list of standard risk phrases used in the safety data sheet

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

Guidelines for safe handling used in the safety data sheet

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P261	Avoid breathing vapours/spray.
P273	Avoid release to the environment.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

A list of additional standard phrases used in the safety data sheet

EUH066	Repeated exposure may cause skin dryness or cracking.
--------	---

The safety data sheet complies with Commission Regulation (EU) 878/2020 of 18 June 2020 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorization and Restriction of Chemicals (REACH) .

SOLBON

Creation date	22nd October 2003	Version	15
Revision date	16th December 2022		

Other important information about human health protection

The mixture should not be used for any purpose other than that for which it is intended (see point 1.2). Because the supplier can not control the specific conditions of use of the mixture, it is the responsibility of the user to adapt the prescribed warnings to local laws and regulations. Safety information describes the product in terms of safety and can not be considered as technical product information.

Key to abbreviations and acronyms used in the safety data sheet

ADR	European agreement concerning the international carriage of dangerous goods by road
BCF	Bioconcentration Factor
CAS	Chemical Abstracts Service
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substance and mixtures
EC	Identification code for each substance listed in EINECS
EC ₅₀	Concentration of a substance when it is affected 50% of the population
EINECS	European Inventory of Existing Commercial Chemical Substances
EmS	Emergency plan
EU	European Union
EuPCS	European Product Categorisation System
IATA	International Air Transport Association
IBC	International Code For The Construction And Equipment of Ships Carrying Dangerous Chemicals
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods
IMO	International Maritime Organization
INCI	International Nomenclature of Cosmetic Ingredients
ISO	International Organization for Standardization
IUPAC	International Union of Pure and Applied Chemistry
LC ₅₀	Lethal concentration of a substance in which it can be expected death of 50% of the population
LD ₅₀	Lethal dose of a substance in which it can be expected death of 50% of the population
log K _{ow}	Octanol-water partition coefficient
NPK	Maximum admissible concentration
OEL	Occupational Exposure Limits
PBT	Persistent, Bioaccumulative and Toxic
PEL	Permissible Exposure Limit
ppm	Parts per million
Press. Gas (Comp.)	Gas under pressure: compressed gas
Press. Gas (Diss.)	Gas under pressure: dissolved gas
Press. Gas (Liq.)	Gas under pressure: liquefied gas
Press. Gas (Ref. Liq.)	Gas under pressure: refrigerated liquefied gas
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Agreement on the transport of dangerous goods by rail
UN	Four-figure identification number of the substance or article taken from the UN Model Regulations
UVCB	Substances of unknown or variable composition, complex reaction products or biological materials
VOC	Volatile organic compounds
vPvB	Very Persistent and very Bioaccumulative
Aerosol	Aerosol
Aquatic Chronic	Hazardous to the aquatic environment (chronic)
Asp. Tox.	Aspiration hazard
Eye Irrit.	Eye irritation



SAFETY DATA SHEET

The safety data sheet complies with Commission Regulation (EU) 878/2020 of 18 June 2020 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorization and Restriction of Chemicals (REACH) .

SOLBON

Creation date	22nd October 2003	Version	15
Revision date	16th December 2022		

Flam. Gas	Flammable gas
Flam. Liq.	Flammable liquid
Press. Gas	Gases under pressure
Skin Irrit.	Skin irritation
STOT SE	Specific target organ toxicity - single exposure

Training guidelines

According to § 103 and § 104 of Act No. 262/2006 Coll., The Labor Code, as amended. Inform the personnel about the recommended ways of use, mandatory protective equipment, first aid and prohibited ways of handling the product.

Recommended restrictions of use

The mixture should not be used for any purpose other than that for which it is intended (see point 1.2). Because the specific conditions of use of the substance are beyond the control of the supplier, it is the responsibility of the user to adapt the prescribed warnings to local laws and regulations. Safety information describes the product in terms of safety and can not be considered as technical product information.

Information about data sources used to compile the Safety Data Sheet

REGULATION (EC) No. 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL (REACH) as amended. REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Data from the manufacturer of the substance / mixture, if available - information from registration dossiers.

The changes (which information has been added, deleted or modified)

Adaptation of BL updated Annex II of the REACH Regulation as amended by Commission Regulation (EU) 2020/878.

Statement

The safety data sheet contains the data needed to ensure safety and health at work and environmental protection. These data correspond to the current state of knowledge and experience and are in accordance with applicable legal regulations. They can not be considered as a guarantee of the suitability and usability of the product for a specific application. The user is responsible for the treatment under existing laws and regulations.